

**RAV 540U** 



# Ravaglioli

**RAV** 535U 540U



SELF LUBRICATING

All pivot points made with self lubricating bushings for long life.

#### **MECHANICAL LOCK**

Mechanical locking device with automatic engagement and pneumatic release, ensuring maximum safety when lift is in standing position.



RAV 535U / 7,000 lbs - Minimum height 3,9" RAV 540U / 9,000 lbs - Minimum height 5,3"



The minimum height from the floor guarantees easy and rapid positioning of the vehicle on the lift. The limited space required by the lift improves safety of the working area. Ideal for mechanical repairs, tyre shops and rapid fit facilities. It is also a good choice for service reception areas.



 No cross rails or torsion bars between lifting platforms (for maximum accessibility in the working area).

1111212121

 Controlled speed during initial lifting and final lowering phase.




#### RAV 535U

## **7,000 lbs**Minimum height 3,9"

Extra low version.

The lift is an ideal choice for low ground clearance vehicles and in particular for extra low spoilers. The lift is recommended for vehicles with variable height, or damaged suspensions.







#### RAV 540U

#### 9,000 lbs Minimum height 5,3"

High capacity model with longer lifting plates.







TECHNICAL DATA		
Voltage		220 / 1Ph / 60 cycles
Motor	hp	3,3
Shipping Weight	lbs	1620 (535) 1660 (540)



### **RAV Equipment U.S.A. Inc.** +1.888.625.4387

+1.888.625.438/ info@ravamerica .com

#### INTERNATIONAL Ravaglioli S.p.A.

40037 Sasso Marconi Fraz. Pontecchio M. P.O.B. 1690 - Bologna - Italia Tel. +39 - 051 - 6781511 Fax +39 - 051 - 846349 rav@ravaglioli.com www.ravaglioli.com

#### **OPTIONS**



#### S 505 A2 (2 x kit) Cross members

To provide safe wheel free lifting of vehicles with narrow lifting points.

Set of pads (4 x kit)

set of pads ( 1 % mit)		
S 505A1	H= 8"	
S 505A5	H= 4 3/4"	
S 505A6	H= 1 1/2"	
S 505A7	H= 3/4"	



